

Direct Burial Splice Kits

FEATURES AND BENEFITS

- Specifically designed for direct burial applications
- Creates a permanent waterproof splice
- A labor saving solution that eliminates epoxies, tapes or separate mastics
- Prevents deterioration of cable and eliminates any problems that can lead to open circuits and cable failure
- All kits include heat shrink tubing with mastic and mechanical connectors to ensure a safe and reliable splice

APPLICATIONS

- Irrigation controls
- Outdoor and landscape lighting
- Sprinkler systems
- Splicing of underground feeder cables
- Repair or extend underground rated conductors such as "UF" and "USE"

UF SPLICE KIT - FOR DIRECT BURIAL

- UL Listed for direct burial
- 600 Volts maximum, 221°F (105°C) temperature rating
- Meets the requirements of the 2014 National Electric Code: Articles: 110.14(B), 300.5(E) and 300.50(D)
- Includes one (1) 4-position mechanical connector and one (1) piece of heat shrink tubing to splice and insulate 14 AWG to 8 AWG UF Cable



Catalog Number	Description	Order Unit	Unit Qty.	Unit Pkg.	Carton Qty.
UFK-14-8	Accommodates: 14/3 without Ground (min.) 8/3 without Ground (max.)	EA	1	BG	24

UF STRETCHER KIT - FOR DIRECT BURIAL

- UL Listed for direct burial
- 600 Volts maximum, 221°F (105°C) temperature rating
- Meets the requirements of the 2014 National Electric Code: Articles: 110.14(B), 300.5(E) and 300.50(D)
- Includes one (1) 4-position 11.5" connector and one (1) piece of heat shrink tubing



Catalog Number	Description	Order Unit	Unit Qty.	Unit Pkg.	Carton Qty.
UFSK-14-8	Accommodates: 14/3 without Ground (min.) 8/3 without Ground (max.)	EA	1	BG	12

COPPER BUTT SPLICE KITS

- UL Listed
- 600 Volts maximum, 221°F (105°C) temperature rating
- Meets the requirements of the 2014 National Electric Code: Articles: 110.14(B), 300.5(E) and 300.50(D)
- Designed to simplify splicing copper conductors



Catalog Number	UL Listed Wire Range of Kit	Description	Order Unit	Unit Qty.	Unit Pkg.	Carton Qty.
CSK-14-8	14 - 8 AWG Copper	Butt Splice Kit includes one (1) Copper Butt Splice Connector and one (1) 4 in. piece of Heat Shrink Tube	EA	1	BG	24
CSK-8-2	8 - 2 AWG Copper	Butt Splice Kit includes one (1) Copper Butt Splice Connector and one (1) 4 in. piece of Heat Shrink Tube	EA	1	BG	24

DUAL RATED BUTT SPLICE KITS - FOR DIRECT BURIAL

- For use with aluminum and copper conductors
- UL Listed
- 600 Volts maximum, 221°F (105°C) temperature rating
- Meets the requirements of the 2014 National Electric Code: Articles: 110.14(B), 300.5(E) and 300.50(D)



Catalog Number	UL Listed Wire Range of Kit	Description	Order Unit	Unit Qty.	Unit Pkg.	Carton Qty.
ASK-8-4	8 - 4 AWG AL/CU	Dual Rated Butt Splice Kit includes one (1) Dual Rated Connector and two (2) Heat Shrink Tubes	EA	1	BG	24
ASK-2-1/0	2 - 1/0 AWG AL/CU	Dual Rated Butt Splice Kit includes one (1) Dual Rated Connector and two (2) Heat Shrink Tubes	EA	1	BG	24
ASK-2/0-250	2/0 - 250 MCM AL/CU	Dual Rated Butt Splice Kit includes one (1) Dual Rated Connector and two (2) Heat Shrink Tubes	EA	1	BG	24