



NOTES:

- ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED
- SEE INSTALLATION SHEET FOR WIRE SIZE AND TOOLING RECOMMENDATIONS
- TIN-PLATED TO INHIBIT CORROSION
- RATED FOR COPPER CONDUCTORS ONLY
- BEVELED ENTRY FOR EASY CABLE INSERTION
- CONNECTORS ARE SUITABLE FOR VOLTAGES UP TO 35 KV
- FOR APPLICATIONS GREATER THAN 2000 VOLTS, CONSULT CABLE MANUFACTURER FOR VOLTAGE STRESS RELIEF INSTRUCTIONS
- CONNECTORS ARE UL LISTED PER UL486A-B FOR POWER APPLICATIONS UP TO 90°C
- CONNECTORS ARE UL LISTED FOR GROUNDING, BONDING, AND DIRECT BURIAL APPLICATIONS PER UL467
- CONNECTORS ARE DESIGNED FOR USE WITH CORRESPONDING BBLB SERIES LUGS
- APPROXIMATE WEIGHT: 0.632 LBS



NO.	ECN	DATE
REVISIONS		

			X						COPPER TUBING
	QTY.		PT.						NAME OR DESCRIPTION
									BOTTOM STACKING LUG for 500 MCM COPPER CONDUCTORS
									REF. DWG'S: 2H52-56437
									H:\2H52\BBLB-050D
									DRAWN BY: DT DATE: 8/8/2023 CHK'D: QJB
									SCALE: 2:3 INTERPRET PER ASME Y14.5-2009 FILE: 2H52
									SIZE: B DWG. NO. BBLB-050D REV. -