

JA 91-8188 SCALE 1: 1

- 2. SEE INSTALLATION SHEET FOR WIRE SIZE AND TOOLING RECOMMENDATIONS
- 3. TIN-PLATED TO INHIBIT CORROSION
- 4. RATED FOR COPPER CONDUCTORS ONLY
- 5. BEVELED ENTRY FOR EASY CABLE INSERTION
- 6. CONNECTORS ARE SUITABLE FOR VOLTAGES UP TO 35 KV
- 7. FOR APPLICATIONS GREATER THAN 2000 VOLTS, CONSULT CABLE MANUFACTURER FOR VOLTAGE STRESS RELIEF INSTRUCTIONS
- 8. CONNECTORS ARE UL LISTED PER UL486A-B FOR POWER APPLICATIONS UP TO 90°C
- 9. CONNECTORS ARE UL LISTED FOR GROUNDING, BONDING, AND DIRECT BURIAL APPLICATIONS PER UL467
- 10. CONNECTORS ARE DESIGNED FOR USE WITH CORRESPONDING BBLS SERIES LUGS
- 11. APPROXIMATE WEIGHT: 0.122 LBS



				Χ		COPPER TUBING			
	QTY. PT				PT.	NAME OR DESCRIPTION			
						BOTTOM STACKING LUG			
							for		
						1/0 AWG COPPER CONDUCTORS			
						REF. DWG'S: 2H52-56429		H:\2F	152\BBLB-1.0D
							DRAWN BY: DT	DATE: 8/8/2023 C	CHK'D: QJB
				0D	o.	PENNŮNION™	SCALE: 3:2 INTER	RPRET PER ASME Y14.5-2009	FILE: 2H52
DATE				.B-1	N. NO	229 WATERFORD STREET	SIZE: B	BBLB-1/0D	REV.
3				BBL	Ö	EDINBORO, PA 16412 USA		DDLD-1/0D	_

ECN

REVISIONS