

THIS DOCUMENT CONTAINS INFORMATION PROPRIETARY TO PENN-UNION CO. LLC. IT IS SUBMITTED IN CONFIDENCE AND IS TO BE USED SOLELY FOR THE PURPOSE FOR WHICH IT IS FURNISHED AND MUST BE RETURNED UPON REQUEST. THIS DOCUMENT AND SUCH INFORMATION IS NOT TO BE REPRODUCED, TRANSMITTED, DISCLOSED, OR USED OTHERWISE IN WHOLE OR IN PART WITHOUT THE EXPRESS CONSENT OF PENN-UNION CO. LLC.

ons D	E	F	APPROX. WEIGHT	Strip Length
		-	(LB)	
.39	1.19	1.00	0.731	2.81
.39	1.19	1.75	0.870	
ALTERNATE LUG CONFIGURATIONS: -45 FOR 45° BENT PAD -90 FOR 90° BENT PAD -FL FOR FLARED BARREL ENTRY -U FOR UNDRILLED PAD EXAMPLE: BBLU-060D-2TC38-NT-FL				
SCALE 1 : 1				
NAME OR DESCRIPTION				
IG BARREL NARROW TONGUE LUG				
for				
600 MCM COPPER CONDUCTORS				
6120	DRAWN BY:			BLU-060D-NT
			: 7/17/2023 ASME Y14.5-2009	2
RD STREET	SIZE: B Ú		-060D-	