

THIS DOCUMENT CONTAINS INFORMATION PROPRIETARY TO PENN-UNION CO. LLC. IT IS SUBMITTED IN CONFIDENCE AND IS TO BE USED SOLELY FOR THE PURPOSE FOR WHICH IT IS FURNISHED AND MUST BE RETURNED UPON REQUEST. THIS DOCUMENT AND SUCH INFORMATION IS NOT TO BE REPRODUCED, TRANSMITTED, DISCLOSED, OR USED OTHERWISE IN WHOLE OR IN PART WITHOUT THE EXPRESS CONSENT OF PENN-UNION CO. LLC.

SNC			APPROX. WEIGHT	STRIP
D	E	F	(LB)	LENGTH
.09	.50	.63	0.032	1.25
.09	.50	.75	0.034	
.08	.61	.75	0.036	
.08	.61	.81	0.040	
.08	.61	1.00	0.040	
.06	.88	1.75	0.061	
-FL FOR FLARED BARREL ENTRY -U FOR UNDRILLED PAD EXAMPLE: BBLU-4D2TC14E2-FL				



for

4 AWG COPPER CONDUCTORS

REF. DWG'S: 2H08-31540, 2H08-55035, 5H08-97763, 2H08-55037, 5H08-97888, 5H08-97792
H:\2H08\BBLU-4D

Image: Constraint of the state of