

COMPLIANT **APPLICATIONS PER UL467**

> THIS DOCUMENT CONTAINS INFORMATION PROPRIETARY TO PENN-UNION CO. LLC. IT IS SUBMITTED IN CONFIDENCE AND IS TO BE USED SOLELY FOR THE PURPOSE FOR WHICH IT IS FURNISHED AND MUST BE RETURNED UPON REQUEST. THIS DOCUMENT AND SUCH INFORMATION IS NOT TO BE REPRODUCED, TRANSMITTED, DISCLOSED, OR USED OTHERWISE IN WHOLE OR IN PART WITHOUT THE EXPRESS CONSENT OF PENN-UNION CO. LLC.

NO.

ECN

REVISIONS

DATE

₹.

SEE .

DIMENSIONS				APPROX. WEIGHT	STRIP
С	D	Е	F	(LB)	LENGTH
2.00	.22	.83	.75	0.220	2.13
2.00	.22	.83	1.00	0.236	
USE BELOW OPTIONAL SUFFIXES FOR ALITERNATE LUG CONFIGURATIONS: -45 FOR 45° BENT PAD -90 FOR 90° BENT PAD -FL FOR FLARED BARREL ENTRY -U FOR UNDRILLED PAD EXAMPLE: BBLZ-030D-2TC14E2-NT-FL					
COPPER TUBING					
NAME OR DESCRIPTION					
LONG BARREL NARROW TONGUE LUG					
for					
300 MCM COPPER CONDUCTORS					
REF. DWG'S: 2HO	2-56137				2\BBLZ-030D-NT
		DRAWN BY:		: 7/20/2023 ASME Y14.5-2009	CHK'D: QJB FILE: 2H02
229 WATERI	UNIOF FORD STREET			-030D-1	
EDINBORO, I	PA 16412 USA		Ž		
IT IS FURNISHED AND MUST BE RETURNED					