

APPLICATIONS PER C22.2 NO.41

THIS DOCUMENT CONTAINS INFORMATION PROPRIETARY TO PENN-UNION CO. LLC. IT IS SUBMITTED IN CONFIDENCE AND IS TO BE USED SOLELY FOR THE PURPOSE FOR WHICH IT IS FURNISHED AND MUST BE RETURNED UPON REQUEST. THIS DOCUMENT AND SUCH INFORMATION IS NOT TO BE REPRODUCED, TRANSMITTED, DISCLOSED, OR USED OTHERWISE IN WHOLE OR IN PART WITHOUT THE EXPRESS CONSENT OF PENN-UNION CO. LLC.

REVISIONS

SEE

EDINBORO, PA

ONS		APPROX. WEIGHT	STRIP
D E	F	(LB)	LENGTH
.13 .50	.75	0.052	1.38
.13 .50	1.00	0.055	
USE BELOW OPTIONAL SUFFIXES FOR ALTERNATE LUG CONFIGURATIONS: -45 FOR 45° BENT PAD -90 FOR 90° BENT PAD -FL FOR FLARED BARREL ENTRY -U FOR UNDRILLED PAD EXAMPLE: BBLZ-2D-2TC14E2-NT-FL			
NG BARREL NARROW TONGUE LUG for			
2 AWG COPPER CONDUCTORS			
6176		H:\2H02	2\BBLZ-2D-NT
DRAWN BY: [		: 7/19/2023	CHK'D: QJB
		ASME Y14.5-2009	
RD STREET 16412 USA	ġ <b>BBL</b>	Z-2D-N	T