

APPLICATIONS PER C22.2 NO.41

THIS DOCUMENT CONTAINS INFORMATION PROPRIETARY TO PENN-UNION CO. LLC. IT IS SUBMITTED IN CONFIDENCE AND IS TO BE USED SOLELY FOR THE PURPOSE FOR WHICH IT IS FURNISHED AND MUST BE RETURNED UPON REQUEST. THIS DOCUMENT AND SUCH INFORMATION IS NOT TO BE REPRODUCED, TRANSMITTED, DISCLOSED, OR USED OTHERWISE IN WHOLE OR IN PART WITHOUT THE EXPRESS CONSENT OF PENN-UNION CO. LLC.

REVISIONS

₹.

EDINBORO, PA

SEE

ons D	E	F	APPROX. WEIGHT	STRIP LENGTH
		-	(LB)	
.17	.64	.75	0.104	1.63
.17	.64	1.00	0.112	
USE BELOW OPTIONAL SUFFIXES FOR ALTERNATE LUG CONFIGURATIONS: -45 FOR 45° BENT PAD -90 FOR 90° BENT PAD -FL FOR FLARED BARREL ENTRY -U FOR UNDRILLED PAD EXAMPLE: BBLZ-3/0D-2TC 14E2-NT-FL				
NAME OR DESCRIPTION				
IG BAR	REL NARR		GUE LUG	
0.00	for			
3/0 AWG COPPER CONDUCTORS				
6152	DRAWN BY:			
	DRAWN BY: M SCALE: 3:2		: 7/19/2023 ASME Y14.5-2009	CHK'D: QJB FILE: 2H02
RD STREET	SIZE: B		-3/0D-1	