











NAME OR DESCRIPTION

## **NOTES:**

- ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED
- SEE INSTALLATION SHEET FOR WIRE SIZE AND TOOLING RECOMMENDATIONS
- TIN-PLATED TO INHIBIT CORROSION
- RATED FOR COPPER CONDUCTORS ONLY 4.
- BEVELED ENTRY FOR EASY CABLE INSERTION
- INSPECTION WINDOW TO ENSURE FULL CABLE INSERTION
- CONNECTORS ARE SUITABLE FOR VOLTAGES UP TO 35 KV
- FOR APPLICATIONS GREATER THAN 2000 VOLTS, CONSULT CABLE MANUFACTURER FOR VOLTAGE STRESS RELIEF INSTRUCTIONS
- CONNECTORS ARE UL LISTED PER UL486A-B AND CSA CERTIFIED PER C22.2 NO.65 FOR POWER APPLICATIONS UP TO 90°C
- 10. CONNECTORS ARE ULLISTED FOR GROUNDING, BONDING, AND DIRECT BURIAL **APPLICATIONS PER UL467**
- 11. CONNECTORS ARE CSA CERTIFIED FOR GROUNDING, BONDING, AND DIRECT BURIAL APPLICATIONS PER C22.2 NO.41



<u> </u>												
							STANDARD BAI	RRELI	<b>NARRO</b>	OW TONGUE LI	JG	
		4 AWG COPPER CONDU								NDUCTORS		
	NO. ECN DATE						REF. DWG'S: 2H03-56180		H:\2H03\BLU-4D-N		4D-NT	
١							PENNUNION  229 WATERFORD STREET EDINBORO, PA 16412 USA	DRAWN	BY: DT	DATE: 7/7/2023	CHK'D:	QJB
5					烂	CAT. NO.		SCALE: 2:1 INTER		RPRET PER ASME Y14.5-2009   FILE:		2H03
					TABLE			SIZE: B	Ö		_	REV.
	REVISIONS				SEE			$\bigoplus \Box$	N O N	BLU-4D-N	l	-
25 AND IS TO BE USED COLEN FOR THE PURPOSE FOR MURCUIT IS FURNISHED AND ANICT DE DETURNED.												

COPPER TUBING

QTY.

PT.