



REV.	CAT. NO.	SUFFIX	STUD HOLE	DIMENSIONS					APPROX. WEIGHT	STRIP
				Α	В	C	D	Е	(LB)	LENGTH
11	BLUA-1/0S2	\$2	1/4	2.17	.86	.88	.23	.84	0.125	
80	BLUA-1/0S3	\$3	5/16	2.17	.86	.88	.23	.84	0.121	1.13
12	BLUA-1/0S	S	3/8	2.17	.86	.87	.23	.84	0.118	1.13
07	BLUA-1/0S1	\$1	1/2	2.44	1.13	1.00	.23	.86	0.130	







NOTES:

- 1. ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED
- 2. SEE INSTALLATION SHEET FOR WIRE SIZE AND TOOLING RECOMMENDATIONS
- 3. TIN-PLATED AND FACTORY PREFILLED WITH OXIDE INHIBITOR
- 4. RATED FOR ALUMINUM AND COPPER CONDUCTORS UP TO 90°C
- 5. BEVELED ENTRY FOR EASY CABLE INSERTION
- 6. END CAPS PROVIDED TO PREVENT FOREIGN MATERIALS FROM ENTERING AND CONTAMINATING THE CONNECTOR PRIOR TO USE
- 7. CONNECTORS ARE SUITABLE FOR VOLTAGES UP TO 35 KV
- 8. FOR APPLICATIONS GREATER THAN 2000 VOLTS, CONSULT CABLE MANUFACTURER FOR VOLTAGE STRESS RELIEF INSTRUCTIONS
- 9. CONNECTORS ARE UL LISTED PER UL486A-B AND CSA CERTIFIED PER C22.2 NO.65 FOR POWER APPLICATIONS UP TO 90°C



NO.	ECN	DATE		
revisions				

				Χ		ALUMINUM TUBING							
	QTY. PT.				PT.	NAME OR DESCRIPTION							
	PENN-CRIMP LUG												
						for							
						1/0 AWG ALUMINUM AND COPPER CONDUCTORS							
						REF. DWG'S: 4H29-44164, 4H29-52764, 4H29-34345, 4H29-45925 H:\4H29\BLUA-1/0S							
						DRAWN BY: DT DATE: 6/27/2023 CHK'D: QJ	Ø						
				出	0.	PENNUMBER SCALE: 3:2 INTERPRET PER ASME Y14.5-2009 FILE: 4H29							
_				TABLE	ž	REV	<i>/</i> .						
				SEE T	:AT	229 WATERFORD STREET SIZE: B O O O BLUA-1/OS LEDINBORO, PA 16412 USA							
				S	\cup	EDIINDUKU, FA 10412 USA \Psi \times D 2							