



NOTES:

1. MANUFACTURED FROM HIGH STRENGTH ALUMINUM ALLOY EXTRUSION
2. ELECTRO-TIN PLATED TO ENSURE MINIMUM CONTACT RESISTANCE AND CORROSION PROTECTION
3. CONNECTORS ARE RATED FOR 600V, 90°C APPLICATIONS
4. THE USE OF OXIDE INHIBITOR IS RECOMMENDED FOR ALL ALUMINUM TERMINATIONS
5. cULus LISTED PER UL486A-B FOR ALUMINUM AND COPPER CONDUCTORS AT 90°C
6. INSTALLATION TORQUE: 120 IN•LB, STRIP LENGTH: .75
7. ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED
8. APPROX. WEIGHT: 0.067 LB



NO.	ECN	DATE	QTY.	PT.	NAME OR DESCRIPTION
9	12187	6/8/2022	2	2	SET SCREW, ALUMINUM, TIN PLATED
8	B21-62	8/16/2021	1	1	LUG BODY, ALUMINUM, TIN PLATED
7	12060	3/30/2021			
6	12052	3/24/2021			
5	12037	2/22/2021			
4	11877	8/21/2019			
3	11611	10/21/2015			
2	11026	9/4/2009			
1	10159C	11/7/1998			
ALUMINUM TERMINAL LUG for 2/0-#14 STR. 2 CONDUCTOR					
REF. DWG'S: 5J06-98672S8 H:\5J06\98672S8_C					
PENNUNION 229 WATERFORD STREET EDINBORO, PA 16412 USA		DRAWN BY: QJB		DATE: 4/24/2023	CHK'D: NAK
		SCALE: 2:1	INTERPRET PER ASME Y14.5-2009		FILE: 5J06
DWG. NO. L2A-2/0		SIZE: B		REV. 9	