



METAL STAMPING TO READ:
 1. PENN-UNION
 2. L2A-250
 3. 250 MCM-6
 4. AL9CU
 5. 

NOTES:

- MANUFACTURED FROM HIGH STRENGTH ALUMINUM ALLOY EXTRUSION
- ELECTRO-TIN PLATED TO ENSURE MINIMUM CONTACT RESISTANCE AND CORROSION PROTECTION
- CONNECTORS ARE RATED FOR 600V, 90°C APPLICATIONS
- THE USE OF OXIDE INHIBITOR IS RECOMMENDED FOR ALL ALUMINUM TERMINATIONS
- cULus LISTED PER UL486A-B FOR ALUMINUM AND COPPER CONDUCTORS AT 90°C
- INSTALLATION TORQUE: 225 IN•LB, STRIP LENGTH: 1.12
- ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED
- APPROX. WEIGHT: 0.212 LB

NO.	ECN	DATE
10	12075	5/6/2021
9	12037	2/22/2021
8	11925	3/5/2020
7	11870	8/2/2019
6	11611	10/21/2015
5	11026	9/4/2009
4	10018	12/11/1996
3	9945	5/16/1996
2	8955	2/24/1988
1	8819	5/14/1986

2	2	SET SCREW, ALUMINUM, TIN PLATED
1	1	LUG BODY, ALUMINUM, TIN PLATED
QTY.	PT.	NAME OR DESCRIPTION
ALUMINUM TERMINAL LUG		
for 250 MCM-#6 STR. 2 CONDUCTOR		
REF. DWG'S: 5J06-98672S2		H:\5J06\98672S2_C
		DRAWN BY: QJB DATE: 4/24/2023 CHK'D: NAK
229 WATERFORD STREET EDINBORO, PA 16412 USA		SCALE: 3:2 INTERPRET PER ASME Y14.5-2009 FILE: 5J06
DWG. NO.	L2A-250	REV. 10

