



NOTES:

1. MANUFACTURED FROM HIGH STRENGTH ALUMINUM ALLOY EXTRUSION
2. ELECTRO-TIN PLATED TO ENSURE MINIMUM CONTACT RESISTANCE AND CORROSION PROTECTION
3. CONNECTORS ARE RATED FOR 600V, 90°C APPLICATIONS
4. THE USE OF OXIDE INHIBITOR IS RECOMMENDED FOR ALL ALUMINUM TERMINATIONS
5. cULus LISTED PER UL486A-B FOR ALUMINUM AND COPPER CONDUCTORS AT 90°C
6. INSTALLATION TORQUE: 225 IN•LB, STRIP LENGTH: 1.25
7. ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED
8. APPROX. WEIGHT: 0.273 LB



NO.	ECN	DATE
9	12037	2/22/2021
8	11925	3/5/2020
5	11870	8/2/2019
4	11611	10/21/2015
3	11026	9/4/2009
2	10159C	11/7/1998
1	9945	5/16/1996

QTY.	PT.	NAME OR DESCRIPTION
2	2	SET SCREW, ALUMINUM, TIN PLATED
1	1	LUG BODY, ALUMINUM, TIN PLATED
ALUMINUM TERMINAL LUG for 350 MCM-#6 STR. 2 CONDUCTOR		
REF. DWG'S: 5J06-98672S3		H:\5J06\98672S3_C
PENNUNION 229 WATERFORD STREET EDINBORO, PA 16412 USA		DRAWN BY: QJB DATE: 4/24/2023 CHK'D: NAK SCALE: 3:2 INTERPRET PER ASME Y14.5-2009 FILE: 5J06
SIZE: B		DWG. NO. L2A-350
		REV. 9