



NOTES:

1. MANUFACTURED FROM HIGH STRENGTH ALUMINUM ALLOY EXTRUSION
2. ELECTRO-TIN PLATED TO ENSURE MINIMUM CONTACT RESISTANCE AND CORROSION PROTECTION
3. CONNECTORS ARE RATED FOR 600V, 90°C APPLICATIONS
4. THE USE OF OXIDE INHIBITOR IS RECOMMENDED FOR ALL ALUMINUM TERMINATIONS
5. cULus LISTED PER UL486A-B FOR ALUMINUM AND COPPER CONDUCTORS AT 90°C
6. INSTALLATION TORQUE: 400 IN•LB, STRIP LENGTH: 1.50
7. ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED
8. APPROX. WEIGHT: 0.544 LB



NO.	ECN	DATE
8	12037	2/22/2021
7	11611	10/21/2015
6	11026	9/4/2009
5	10159C	11/7/1998
4	10089	7/9/1997
3	8819	5/14/1986

QTY.	PT.	NAME OR DESCRIPTION
2	2	SET SCREW, ALUMINUM, TIN PLATED
1	1	LUG BODY, ALUMINUM, TIN PLATED
<b>ALUMINUM TERMINAL LUG</b> for 600 MCM-#2 STR. 2 CONDUCTOR		
REF. DWG'S: 5J06-98672S5		H:\5J06\98672S5_C
DRAWN BY: QJB		DATE: 4/24/2023
SCALE: 1:1		CHK'D: NAK
SIZE: B		INTERPRET PER ASME Y14.5-2009
FILE: 5J06		
DWG. NO.	L2A-600	
REV.	8	