



- NOTES:
1. MANUFACTURED FROM HIGH STRENGTH ALUMINUM ALLOY EXTRUSION
 2. ELECTRO-TIN PLATED TO ENSURE MINIMUM CONTACT RESISTANCE AND CORROSION PROTECTION
 3. CONNECTORS ARE RATED FOR 600V, 90°C APPLICATIONS
 4. THE USE OF OXIDE INHIBITOR IS RECOMMENDED FOR ALL ALUMINUM TERMINATIONS
 5. cULus LISTED PER UL486A-B FOR ALUMINUM AND COPPER CONDUCTORS AT 90°C
 6. INSTALLATION TORQUE: 400 IN•LB, STRIP LENGTH: 1.57
 7. ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED
 8. APPROX. WEIGHT: 1.588 LB



NO.	ECN	DATE
REVISIONS		

	6	2	SET SCREW, ALUMINUM, TIN PLATED
	1	1	LUG BODY, ALUMINUM, TIN PLATED
QTY.	PT.	NAME OR DESCRIPTION	
ALUMINUM MECHANICAL LUG for 2 AWG-600 MCM AL9CU			
REF. DWG'S: 5J17-96403		H:\5J17\L3A-600-2	
 229 WATERFORD STREET EDINBORO, PA 16412 USA		DRAWN BY: DT	DATE: 9/13/2023
		CHK'D: QJB	FILE: 5J17
SIZE: B		INTERPRET PER ASME Y14.5-2009	
DWG. NO. L3A-600-2		REV. -	