



NOTES:

1. MANUFACTURED FROM HIGH STRENGTH ALUMINUM ALLOY EXTRUSION
2. ELECTRO-TIN PLATED TO ENSURE MINIMUM CONTACT RESISTANCE AND CORROSION PROTECTION
3. CONNECTORS ARE RATED FOR 600V, 90°C APPLICATIONS
4. THE USE OF OXIDE INHIBITOR IS RECOMMENDED FOR ALL ALUMINUM TERMINATIONS
5. cULus LISTED PER UL486A-B FOR ALUMINUM AND COPPER CONDUCTORS AT 90°C
6. INSTALLATION TORQUE: 275 IN•LB, STRIP LENGTH: 1.12
7. ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED
8. APPROX. WEIGHT: 0.113 LB



NO.	ECN	DATE
2	12055	3/26/2021
1	B20-25	10/14/2020

QTY.	PT.	NAME OR DESCRIPTION
1	2	SET SCREW, ALUMINUM, TIN PLATED
1	1	LUG BODY, ALUMINUM, TIN PLATED
ALUMINUM TERMINAL LUG		
for 250 MCM-#6 STR.		
REF. DWG'S: 5J03-96608		H:\5J03\96608_C
PENNUNION 229 WATERFORD STREET EDINBORO, PA 16412 USA		DRAWN BY: QJB DATE: 4/24/2023 CHK'D: NAK
SCALE: 3:2 INTERPRET PER ASME Y14.5-2009 FILE: 5J03		SIZE: B
DWG. NO. LA-250		REV. 2