



- METAL STAMPING TO READ:
1. PENN-UNION
  2. LA-350
  3. 350 MCM-6
  4. AL9CU
  - 5.

NOTES:

1. MANUFACTURED FROM HIGH STRENGTH ALUMINUM ALLOY EXTRUSION
2. ELECTRO-TIN PLATED TO ENSURE MINIMUM CONTACT RESISTANCE AND CORROSION PROTECTION
3. CONNECTORS ARE RATED FOR 600V, 90°C APPLICATIONS
4. THE USE OF OXIDE INHIBITOR IS RECOMMENDED FOR ALL ALUMINUM TERMINATIONS
5. cULus LISTED PER UL486A-B FOR ALUMINUM AND COPPER CONDUCTORS AT 90°C
6. INSTALLATION TORQUE: 275 IN•LB, STRIP LENGTH: 1.25
7. ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED
8. APPROX. WEIGHT: 0.152 LB



NO.	ECN	DATE
1	12055	3/26/2021
REVISIONS		

QTY.	PT.	NAME OR DESCRIPTION
1	2	SET SCREW, ALUMINUM, TIN PLATED
1	1	LUG BODY, ALUMINUM, TIN PLATED
<b>ALUMINUM TERMINAL LUG</b> for 350 MCM-#6 STR.		
REF. DWG'S: 5J03-96609		H:\5J03\96609_C
DRAWN BY: QJB		DATE: 4/24/2023
SCALE: 3:2		CHK'D: NAK
SIZE: B		INTERPRET PER ASME Y14.5-2009
DWG. NO. LA-350		FILE: 5J03
REV. 1		

