





(2X) 1/2-13 X 2 HH BOLT

(2X) 1/2 FLAT WASHER

CLAMP

BODY



STAMPING TO READ:
 1. PCAA-25
 2. 3/0 STR. TO 397.5 18/1 ACSR
 3. PENN-UNION

CONDUCTOR RANGE		INSTALLATION TORQUE
MAIN	TAP	
3/0 STR.-400 MCM 3/0-397.5 18/1 ACSR 4-2/0 STR. AR	3/0 STR.-400 MCM 3/0-397.5 18/1 ACSR 4-2/0 STR. AR	480 IN•LB

NOTE:

- MANUFACTURED FROM HIGH STRENGTH ALUMINUM EXTRUDED ALLOY
- FOR ALUMINUM, COPPER, ACSR, AND AR CONDUCTORS
 - ALL ALUMINUM CABLE RATING WITH PREFORMED ARMOR RODS
- DESIGNED FOR TAP AND PARALLEL CONNECTIONS
- ASSEMBLED WITH HIGH STRENGTH STAINLESS STEEL BOLTS AND FLAT WASHERS
- ALL CONDUCTOR CONTACT SURFACES HAVE SERRATED GROVES TO PROVIDE INCREASED CONDUCTOR CONTACT AND IMPROVE MECHANICAL PERFORMANCE
- FOR ALUMINUM TO COPPER APPLICATIONS, IT IS RECOMMENDED TO INSTALL THE ALUMINUM CONDUCTOR ABOVE THE COPPER CONDUCTOR TO MINIMIZE CORROSION
- FOR FACTORY APPLIED OXIDE INHIBITOR, SUFFIX CATALOG NUMBER WITH "-BF"
- FOR TIN PLATING ON BODY AND CLAMP, SUFFIX CATALOG NUMBER WITH "-TN"
- CONFORMS TO ANSI C119.4, CLASS AA CURRENT, CLASS 3 TENSION WHEN PROPERLY INSTALLED
- ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED
- APPROX. WEIGHT: 1.481 LB

NO.	ECN	DATE
REVISIONS		

QTY.	PT.	NAME OR DESCRIPTION
		ALUM. PARALLEL CLAMP ASS'Y
REF. DWG'S: 5E16-97155		H:\H:\5E16\97155_C
DRAWN BY: QJB		DATE: 2/16/2023
SCALE: 2:3		INTERPRET PER ASME Y14.5-2009
SIZE: B		FILE: 5E16
DWG. NO. PCAA-25		REV. -
229 WATERFORD STREET EDINBORO, PA 16412 USA		