



NOTES:

1. FOR TIN PLATING, SUFFIX CATALOG NUMBER WITH "-TN"
2. ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED
3. cULus LISTED PER UL486A-B FOR POWER APPLICATIONS UP TO 90°C
4. cULus LISTED PER UL467 FOR GROUNDING, BONDING, AND DIRECT BURIAL
5. INSTALLATION TORQUE: 150 IN•LB
6. HEX SIZE: 7/32
7. APPROX. WEIGHT: 0.226 LB



NO.	ECN	DATE
5	12235	2/22/2023
4	12152	10/29/2021
3	11860	7/2/2019
2	11745	4/4/2018
1	11705	8/24/2017

QTY.	PT.	NAME OR DESCRIPTION
1	3	SET SCREW, STEEL, BLUE ZINC PLATED
1	2	LUG TONGUE, COPPER
1	1	LUG BODY, COPPER
<b>COPPER MECHANICAL LUG</b>		
for <b>4/0-6 STR. COPPER CONDUCTORS</b>		
REF. DWG'S: 5506-55833		H:\5506\SLU225
<b>PENNUNION</b> 229 WATERFORD STREET EDINBORO, PA 16412 USA		DRAWN BY: CLT    DATE: 7/19/2023    CHK'D: QJB
SCALE: 3:2		INTERPRET PER ASME Y14.5-2009    FILE: 5506
DWG. NO.	SLU-225	REV. 5